

## **TECHNICAL SPECIFICATIONS**

DEMOMINATION	REFERENCE	
FUTURA STANDARD HAND DRYER SENSOR OPERATED BRIGHT STAINLESS STEEL	AA16000	
DESCRIPTION		
HANDDRYER MODEL STANDARD FUTUR MADE IN AISI 304 STAINLESS STEEL COVER WITH BRIGHT FINISH AND BODY IN GREY POLICARBONATE. WORKS BY PLACING HANDS BELOW THE SENSOR UP TO TWO MINUTES.  ELECTRICAL SCHEME	JOFEL	
1 INTERRUPTOR TÉRMICO (EN RESISTENCIA) 2 FUSIBLE TERMICO (EN RESISTENCIA) 3 RESISTENCIA 1990 v 220 V - 50 Hz 4 INTERRUPTOR TÉRMICO (EN MOTOR) 5 MOTOR 220 V - 50 Hz 6 CIRCLITO ELECTRONICO FOR INTERARROJOS		

CHARACTERISTICS		
DIMENSIONS (mm)	310 x 230 x 140	
WEIGHT (Kg)	3,7	
MATERIALS	COVER IN AISI 304 STAINLESS STEEL BRIGHT 1,2 mm thickness, INTERNAL BODY MADE IN POLICARBONATE	
CAPACITY	AIRFLOW: 40 l/sec	
ELECTRICS	POWER 1800 W. ; VOLTAGE: 230 V 50/60 Hz. 2 COIL ENGINES: POWER 130 W. ; VOLTAGE: 230 V 50/60 Hz.	
REMARKS	PACKING: 1 UD PACKAGING 2 UDS PACKING	APROVED BY:  I+D DEPARTMENT  DATE:  23/05/2004