




TECHNICAL DATA SHEET

NAME	REFERENCE
ABS HAND DRYER TIFON, HIGH PERFORMANCE	AA25650
DESCRIPTION	
<p>MADE OF ANTIBACTERIAL ABS OF HIGH QUALITY AND RESISTANCE</p> <p>LARGE HEPA FILTER H14, LONG LASTING LIFE</p> <p>AUTOMATIC EVAPORATION OF WATER COLLECTED</p> <p>SECURITY TIMER WITH AUTOMATIC SWITCH OFF</p> <p>IF ROOM TEMPERATURE IS >25°C: HEATING ELEMENT SWITCHES OFF AUTOMATICALLY</p> <p>LUMINOUS DISPLAY WITH ALARM TO NOTICE ANY INCIDENT</p> <p>REDUCED DIMENSIONS, ENERGY SAVING, AIR SPEED 540 km/h</p>	
	EAN CODE
	8427950354656

CHARACTERISTICS					
NET (without packaging)	DIMENSIONS (mm)	HEIGHT: 540	WIDTH: 320	DEPTH: 180	
	WEIGHT (Kg)	7,215			
GROSS (with packaging)	DIMENSIONS (mm)	HEIGHT: 605	WIDTH: 380	DEPTH: 270	
	WEIGHT (Kg)	8,485			
MATERIALS	ANTIBACTERIAL ABS +PC+ PBT V0				
COLOUR / FINISH	BLACK				
ELECTRICAL FEATURES	VOLTAGE: 220-240 V	*AIR SPEED: 540 Km / HOUR			
	FREQUENCY: 50-60 Hz.	EFFICIENT AIRFLOW: 220 m ³ / HOUR			
ELECTRICAL FEATURES	CONSUMPTION: 5,2 A - 7,5 A	*SOUND PRESSURE: 65,6 dBA			
	MOTOR POWER: 1000 W	AIR TEMPERATURE: 40° C			
	AIR HEATING ELEMENT POWER: 500 W	ELECTRICAL INSULATION: CLASS II			
	EVAPORATOR HEATING ELEMENT P: 50 W	CERTIFICATIONS: GS - CE - SGS			
	TOTAL POWER: 1550 W	PROTECTION DEGREE: IP21			
	MOTOR RPM : 30.000	TYPE OF MOTOR: universal			
	COMMENTS	DRYING TIME 10 seconds			
	PACKAGING	SINGLE UNIT PACKAGING			Approved by: Quality Control Dept.
			DATE: 27/10/2017		

*Sound pressure measured at a distance of 2 m outdoors

*Air speed is measured by means of anemometric probe placed at air outlet

*Tests have been carried out following UNE rules at the laboratories of the Technical University of Valencia