





TECHNICAL DATA SHEET

NAME	REFERENCE
PUSH BUTTON OPERATED HAND DRYER IBERO BRIGHT INOX	AA91000
DESCRIPTION	
TRADITIONAL HAND DRYER OF HIGH QUALITY AND PERFORMANCE	
HIGH QUALITY BRIGHT INOX MANUALLY OPERATED START, AUTOMATIC STOP CLASS II: NO GROUNDING WIRE REQUIRED, PLACED 0,6 mts FROM WATER POINT DOUBLE ELECTRICAL INSULATION	
ELECTRICAL SCHEME	
 <p>1. THERMAL FUSE 2. THERMAL CUT-OFF (IN HEATING ELEMENT) 3. HEATING ELEMENT POWER 1800 W 230 V- 50 HZ 4. THERMAL CUT-OFF (IN MOTOR) 5. MOTOR 230 V - 50 HZ 6. TIMER SWITCH</p>	EAN CODE 8427950323058

CHARACTERISTICS				
NET (without packaging)	DIMENSIONS (mm)	HEIGHT: 220	WIDTH: 280	DEPTH: 210
	WEIGHT (Kg)	3,665		
GROSS (with packaging)	DIMENSIONS (mm)	HEIGHT: 85	WIDTH: 345	DEPTH: 295
	WEIGHT (Kg)	4,360		
MATERIALS	BRIGHT INOX AISI 304 COVER INTERNAL COMPONENTS IN ABS AND POLYCARBONATE "V0" PUSH BUTTON AND NOZZLE IN CHROME ABS			
COLOUR / FINISH	BRIGHT INOX COVER CHROME PUSH BUTTON AND NOZZLE			
ELECTRICAL FEATURES	VOLTAGE: 230V. AC FREQUENCY: 50 Hz. CONSUMPTION: 8,8 Amp. MOTOR POWER: 200 W. RESISTOR POWER: 1800 W. TOTAL POWER: 2000 W. MOTOR RPM: 4250 TYPE OF MOTOR : BRUSHED		AIRSPEED: 121 Km/HOUR EFFICIENT AIRFLOW: 300 m³/HOUR SOUND PRESSURE: 77,5 Db. AIR TEMPERATURE: 54,1 °C (at a distance of 10 cm) ELECTRICAL ISULATION: CLASS II CERTIFICATIONS: TÜV, GS, UL AND CE PROTECTION RATING: IP23	
	FIXING	BY MEANS OF FOUR SCREWS AND FOUR WALL PLUGS - INCLUDED		
PACKAGING	SINGLE UNIT PACKAGING.		Approved by: Quality Control Dept	
			DATE: 12/05/2015	